



Version: 1.1
Date: 12.02.2020

Product Datasheet OILEX Drum Pads

Technical Data

Criteria	OILEX Pad drum 60-60v	OILEX Pad drum 200-60v
Filling material	OILEX Binding Agent*	OILEX Binding Agent*
Quantity	1,6l	4,5l
Absorption capacity	approx. 0,8 – 1,05 l oil	approx. 2,3 - 3,0 l oil
Material of casing	Spun fleece 60g/m ²	
Absorption rate	Immediate absorption	
Colour	white or orange/grey	
Dimensions	37cm	57cm
Weight	approx. 0,21 kg	approx. 0,6 kg
Number of chambers	2	3

- The OILEX Drum Pads can be reused multiple times until their full absorption capacity is reached.
- The casing of the Pads consists of a robust fleece material that is tear resistant as well as dust-proof, while at the same time permeable to oils, fuels etc. After a short contact time the spilled substance permeates the casing of the pad and gets effectively absorbed by the filling material (OILEX Binding Agent).
- High visibility due to use of signal colors.
- The OILEX Pads consists of multiple chambers in order to ensure an optimal distribution of the binding agent.

WHATEVER YOU SPILL

- The OILEX Pads are filled with the highly effective binding agent OILEX and therefore well suited for absorbing all kinds of oils, fuels and a wide range of chemicals (for detailed information on our binding agent OILEX, please see separate product datasheet).
-

WHEREVER YOU SPILL

- The Oilex Drum Pads are well suited for preventative use, when barrel pumps have to be changed or taken off.
- The Pads have cutouts for the bungholes of the barrels.



Instructions for use

- Briefly shake up the OILEX Drum Pads before use and place evenly on the barrel.

Disposal

- The used OILEX Drum Pads have to be disposed of according to the applicable waste management laws.
- The casing of the Pads can be incinerated.

Storage

- The OILEX Pads should be stored in dry conditions.
- Storage life of the binding agent is at least 5 years.
- In order to avoid damage to the casing, OILEX Pads should not come in contact with sharp-edged objects during storage and handling.

Safety Information

- none

Product Variants

Category	Product	Diameter	Product No.	Are of use	Chambers
OILEX Pad drum	60-60v	ca. 37 cm	Ox2105	Standard 60l barrels	2
OILEX Pad drum	200-60v	ca. 57 cm	Ox2106	Standard 200l barrels	3



Selected Product Pictures



OILEX Pad drum 200-60v



OILEX Pad drum 60-60v

*The OILEX binding agent is 100% organic, consisting of a hydrophobic biogenic sediment. Some technical data may therefore vary slightly. Its effectiveness depends on the substances that have to be absorbed. The applicable waste management laws have to be complied with.