



## STYLE 1102(G) GAPSEAL® TAPE

High Density PTFE Gas Tape ~ White, Yellow, Pink Tape



### Physical Properties:

**GAPSEAL®** tape is made of soft, pliable, higher density PTFE (Polytetrafluoroethylene) resins, and with its highest quality, it is easier to install and effect a seal, will not leak due to vibration or severe chemical contact. For easily recognition, it can be cream yellow and pink colored with indivisible pigment; and the white tape is 100% PTFE made of, complies with FDA 21 CFR 177.1550 (PTFE) food requirements.

**GAPSEAL®** tape is a non-corrosive, low coefficient of friction, odorless that stops leakage through threads. It may be used on steam, salt water, air, fuels, all acids, alkalies and solvent. It also can be used on natural gas, propane or butane and petroleum distillates.

**GAPSEAL®** tape is ULC (Underwriter Lab. of Canada) listed, UL listed, and certified by CSA (Canadian Standards Association), DVGW (Deutsche Vereinigung des Gas-und Wasserfaches e.V.) and JIS (Japanese Industrial Standard). It also meets MIL-T-27730A, DIN EN751-3, and BS-7786 standards.

### Its Features Are:

- Low coefficient of friction, no valve drag
- Temperatures from -450°F to +600°F
- Virtually inert to all chemicals,
- Non-corrosive, non-flammable
- Molds easily, lasts longer, easier to install
- Self-lubricating
- Minimum inventory required
- No waste



### Available Sizes:

**Thickness:** 0.1mm

**Width:** 1/2", 3/4", 1",  
12mm, 19mm, 25mm

**Length:** 260", 480", 520",  
10M, 12M

Other sizes can be quoted.

### Approval:



MH27173



1222774



MH 45069



NO-9143BMD427



JQTW 0102

※ Remarks: UL, DVGW & JIS are the approvals for white tape only.



**YEU MING TAI  
CHEM. IND'L CO., LTD.**

P.O. BOX 46-196  
TAICHUNG INDUSTRIAL PARK,  
TAICHUNG, TAIWAN (40799)

Tel: 886-4-23580021  
Fax: 886-4-23596963  
Email: ymt@www.ymt.com.tw  
Http:// www.ymt.com.tw